Temperature Calibration Report

| Customer: | Pacific Marine Center / NOAA | | | | |
|--|------------------------------|-----------|--------------|---------|----------------------|
| Job Number: | 71346 | [| Date of Rep | ort: | 11/14/2012 |
| Model Number | SBE 38 | [| Serial Numb | er: | 3845921-0380 |
| Temperature sensors are normally calibrated 'as received', without adjustments, allowing a determination sensor drift. If the calibration identifies a problem, then a second calibration is performed after work is completed. The 'as received' calibration is not performed if the sensor is damaged or non-functional, or by customer request. An 'as received' calibration certificate is provided, listing coefficients to convert sensor frequency to temperature. Users | | | | | |
| must choose whether the 'as received' calibration or the previous calibration better represents the sensor condition during deployment. In SEASOFT enter the chosen coefficients. The coefficient 'offset' allows a small correction for drift between calibrations (consult the SEASOFT manual). Calibration coefficients obtained after a repair apply only to subsequent data. 'AS RECEIVED CALIBRATION' Performed Not Performed | | | | | |
| Date: |] | Drift sin | ce last cal: | | Degrees Celsius/year |
| Comments: | _ | | • | | |
| 'CALIBRATION A | AFTER REPAIR' | | ✓ Per | rformed | □ Not Performed |
| Date: 11/14/2012 | 2 | Drift sin | ce Last cal: | N/A | Degrees Celsius/year |
| Comments: The temperature r | orobe was replaced | I | | | |