## Biospherical Instruments Inc.

## CALIBRATION CERTIFICATE

Calibration Date Model Number Serial Number Operator Standard Lamp	2/16/2010 QSR2200 20128 TPC GS-1024(8/28/08)				
Probe Excitation Voltage Range:		6	_ to	18	_VDC(+)
Output Polarity:	Positive				
Probe Conditions at Calibration(in air):					
Calibration Voltage: Probe Current:		6 3.4	VI m	DC(+) A	
Probe Output Voltage:					
Probe Illuminated Probe Dark Probe Net Response RG780		85.5 1.8 83.7 2.3	m m m	V V	
Corrected Lamp Output:					
Output In Air (same condition as calibration):					
	9.271E+15 quanta/cm²sec				
0.01540 uE/cm <sup>2</sup> sec					
Calibration Scale Factor: (To calculate irradiance, divide the net voltage reading in Volts by this value.)					
Dry:	9.0302E-18 5.4380E+00	V/(quanta/cm²sec) V/(uE/cm²sec)			

## Notes:

- 1. Annual calibration is recommended.
- Calibration is performed using a Standard of Spectral Irradiance traceable to the National Institute of Standards and Technology (NIST).
- 3. The collector should be cleaned frequently with alcohol.
- 4. Calibration was performed with customer cable, when available.