

The YOUNG Model 81000 Ultrasonic Anemometer is a 3-axis, no moving parts wind sensor. It is perfectly suited for applications requiring fast response, high resolution and three-dimensional wind measurement.

The sensor features durable, corrosion-resistant construction with 3 opposing pairs of ultrasonic transducers supported by stainless steel members. The transducers are arranged so that measurements are made through a common volume. A fast, 160 Hz internal sampling rate ensures superior measurement resolution. Output rates from 4 to 32 Hz may be selected. Each 81000 is individually wind-tunnel tested and calibrated to compensate for wind shadow effects of the support structure.

Model 81000 features four voltage output channels. Serial RS-232 and RS-485 outputs are available as well. For applications requiring synchronized analog measurements, **Model 81000V** includes four voltage input channels instead of voltage outputs. Wind, sonic temperature and voltage input data are transmitted serially. For each model, a variety of preset or custom output format options may be selected by the user.

Both models install on standard 1 inch pipe. Wiring connections are housed in a convenient weatherproof junction box.



Specifications

Wind Speed: 0 to 40 m/s (0 to 90 mph)
 Resolution: 0.01 m/s
 Threshold: 0.01 m/s
 Accuracy: $\pm 1\%$ rms ± 0.05 m/s (0 to 30 m/s)
 $\pm 3\%$ rms (30 to 40 m/s)

Wind Direction: 0 to 360 degrees
 Elevation Range: ± 60 degrees
 Resolution: 0.1 degree
 Accuracy: ± 2 degrees (1 to 30 m/s)
 ± 5 degrees (30 to 40 m/s)

Speed of Sound: 300 to 360 m/s
 Resolution: 0.01 m/s
 Accuracy: $\pm 0.1\%$ rms ± 0.05 m/s (0 to 30 m/s)

Sonic Temperature: -50 to +50 °C
 Resolution: 0.01 °C
 Accuracy: ± 2 °C (0 to 30 m/s)

Serial Output:

RS-232 or RS-485
 1200 to 38400 baud
 4 to 32 Hz (user-selected)
 User Programmable ASCII output configuration
 (select from U, V, W, Speed of sound, Sonic temperature, 2D speed, 3D speed, Azimuth, Elevation)

Preset outputs:

NMEA- Marine Standard
 RMYT- Young Wind Tracker
Units: m/s, cm/s, MPH, Knots, Km/hr

Analog Voltage Outputs (81000):

4 voltage outputs, 0 to 5000 mV
 (select from U, V, W, Sonic temperature or Speed, Azimuth, Elevation, Sonic temperature)

Voltage Input (81000V):

Range: 0 to 5000 mV, V1 & V2
 0 to 1000 mV, V3 & V4
 Resolution: 1 part in 4000
 Accuracy: $\pm 0.1\%$ of full scale

Power Requirement:

12 to 24 VDC, 110 mA

Operating Temperature:

-50 to +50 °C

Dimensions:

56cm high x 17cm radius (3 support arms)
 Weight: 1.7 kg (3.8 lb)
 Shipping Weight: 4.5 kg (10 lb)

Ordering Information

MODEL

ULTRASONIC ANEMOMETER- VOLTAGE & SERIAL OUTPUTS..... **81000**

ULTRASONIC ANEMOMETER- VOLTAGE INPUTS, SERIAL OUTPUTS ONLY..... **81000V**



Complies with applicable CE Directives



R. M. YOUNG COMPANY
 2801 Aero Park Drive
 Traverse City, Michigan 49686 USA
 TEL: (231) 946-3980 FAX: (231) 946-4772
 E-mail: met.sales@youngusa.com
 Web Site: www.youngusa.com