



Order form
Purchaser

Valid from September 2011
Order no

Vaisala INTERCAP® Humidity and Temperature Probe HMP60

Vaisala INTERCAP® Humidity and Temperature Probe		HMP60																		PRICE
1	Output signals	0...1 V 0...2.5 V 0...5 V 1 ...5V Scaling for 4..20 mA converter (channel 1 only) RS485	A B C D I R																	
2	Measured parameter for channel 1	RS485 RH T (-40 ... +60 °C) Td (-40 ... +60 °C)		0 1 2 3																
3	Measured parameter for channel 2	RS485 or current interface RH T (-40 ... +60 °C) Td (-40 ... +60 °C)		0 1 2 3																
4	Sensor protection	Plastic grid with filter Plastic grid Stainless steel sintered filter			A B C															
5	Accessories	No accessories Pair of plastic nuts Duct installation kit 215619		0 1 3																
6	Humidity sensor	Intericap				A														
7	Probe cable length	No cable 60 °C cable 0.3 m HMP50Z032 60 °C cable 3 m HMP50Z30A 180 °C FEP cable 3m 226902																		
8	User guide	No user guide Multilingual quick guide																		
9	Loop power converter	No converter 4...20 mA loop power converter																		
																			TOTAL	
																			QTY	
																			TOTAL VALUE	

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMP60	A	1	2	A	0	A	1	B	0
-------	---	---	---	---	---	---	---	---	---